

## Specification

S.NO	Description of goods	Qty
1.	<p><b>BINOCULAR MICROSCOPE</b>            Binocular Microscope            “Mechanical Stage            4 x Objective Lenses            2 x 10x Wide-Field Eyepieces            50 x Plain Slides            Immersion Oil            Power Cord            Limited 2-Year Warranty            Cover Microscope            Clean Cloth            Cover Slip            Two 10x wide field eyepieces            Two 10x wide field eyepieces, one with pointer            4x, 10x, 40x, and 100x achromatic objectives            100x objective requires immersion oil for maximum resolution            Four-position click-stop turret            40x, 100x, 400x, and 1000x magnification with 10x eyepieces</p>	7pcs
2.	<p><b>MICROSCOPE WITH OIL IMMERSION</b>  <b>BINOCULAR MICROSCOPE</b> is supplied with quadruple revolving nose piece, coaxial mechanical stage, binocular head with hard coated prisms, graduated precise slow motion. the microscopes has in built light arrangement having 6v-20w halogen lamp and solid state light control arrangement complete in box with following optics.            Eye: W.F. 10x (paired)            Objectives: 5x, 10x, 45x (SL), 100x (SL) Oil immersion            (a) Completes as above with A grade Indian optics.            (b) Completes as above with Indian optics &amp; 100x oil immersion having imported lenses.</p>	15pcs
3.	<p><b>MONOCULAR MICROSCOPE WITH EMERSION LENS</b>            Wide field 10x /18mm eyepiece.            45° inclined monocular viewing head rotates 360° for easy sharing by more than one student.            DIN standard 4x (0.10 N.A.), 10x (0.25 N.A.), 40xR (0.65 N.A.) and 100xR oil immersion (1.25 N.A.) semi-plan objectives.</p>	14pcs
4.	<p><b>X-RAY VIEW BOX</b>            Application Home Purpose, Veterinary Purpose, Clinical, Hospital.            Model Zedx-a101 Led X Ray View Box (single Film)            Thickness Approx. 4.5cm.            Input voltage AC100-250V.            Light frequency 50 KHz.            Brightness 4000 lux.            LED light source 50.000 hours.</p>	1pcs
5.	<b>SAHLI’S SQUARE TUBE</b>	7 pcs

6.	INCUBATOR Temperature range 350C above ambient to 600C with temperature accuracy $\pm 10C$ . ) Temperature range ambient + 50 C above ambient to 600 C. Temperature should be controlled by best quality thermostatic control and digital display. Inner chamber made of stainless steel (S. S.	1pcs
7.	WINTROBE'S TUBE	14 pcs
8.	PASTEUR'S PIPETTE	1pkt(500pcs)
9.	CENTRIFUGE GRADUATED MACHINE Speed regulation range for centrifuge tubes 100-3000 rpm ( $1610 \times g$ ) Chamber diameter 335 mm Overall dimensions (WxDxH) 420 x 495 x 235 mm Weight 11.8 kg Nominal operating voltage 230 V, 50/60 Hz or 120 V, 50/60 Hz	1pcs
10.	WESTRGREN'S PIPETTE	30pcs
11.	WESTRGREN'S STAND	22pcs
12.	URINOMETER	11pcs
13.	AUTOCLAVE The autoclave series has a chamber volume range 20liters. The autoclave operates with saturated steam as the sterilizing agent with a temperature range from 105 °C (221°F) to 138 °C (280 °F).	01pcs
14.	ULTRAVIOLET LAMP	01pcs
15.	BP APPARATUS Brand-ELCO	30pcs
16.	STETHOSCOPE	30pcs
17.	TONGUE DEPRESSOR	1pkt (100pcs)
18.	STOP WATCH	29pcs
19.	THERMOMETER	25pcs
20.	HOT AIR OVEN Capacity 250 Litre. Temp range: +5°C to 200°C. Control accuracy: $\pm 0.5^\circ C$ .	01pcs
21.	BUNSEM BURNER	30pcs
22.	STERILE VESSELS / BOTTLE TO COLLECT SAMPLES	100pcs
23.	TORCH	06pcs
24.	KNEE HAMMER	06pcs
25.	MEASURING TAPE	12pcs
26.	ENT EXAMINATION SET	02pcs
27.	REFLECTORS (MIRRORS)	06pcs
28.	TUNING FORKS	02pcs
29.	NASAL SPECULUM	10pcs
30.	LARYNGOSCOPE	01pcs
31.	CATHETERS Foley	10pcs
32.	PROBES	10pcs
33.	HBS AG KIT	100pcs

34.	HIV KIT – TRIDOT	100pcs
35.	CT AND BT KIT	100pcs
36.	PH INDICATOR PAPER STRIPS	100 (1pkt)
37.	LFT Kit	01Kit
38.	BLOOD SUGAR KIT	01Kit
39.	LIPID PROFILE,	01Kit
40.	KFT KIT	01Kit
41.	SYRINGE NEEDLE DESTROYER	02pcs
42.	GLASS JARS WITH LID OF DIFFERENT SIZES	200pcs
43.	RUBBER TEAT	200pcs
44.	MAGNIFYING LENS	10pcs
45.	WATER BATH	02pcs
46.	MULTI STIX	100pcs
47.	STERILE DISPOSABLE LANCET NEEDLE	01pcs
48.	GLASS ROD	20pcs