

Specifications for Media Equipment:-

S.NO.	Items	Specification	QTY
1	SONY CAMCORDER Z90	<p>General:</p> <p>Mass- Approx. 1020g (with lens hood, eyecup)</p> <p>Dimensions (W x H x D) - 121.0mm×104.0mm×274.5mm (With the accessories (lens hood, large eyecup), excluding the grip belt and including the projecting parts)</p> <p>Power Requirements- DC In: 8.4V</p> <p>Battery: 7.4V</p> <p>Power Consumption- Approx. 6.5 W(while recording with viewfinder and XAVC QFHD 2160/30p 60Mbps)</p> <p>Operating Temperature- 0°C to 40°C 32°F to 104°F</p> <p>Battery Operating Time- Approx. 140min. with NP-FV70A battery (while recording with LCD, XAVC QFHD 2160/30p, 60Mbps)</p> <p>Recording Format (Video)- XAVC QFHD : MPEG-4 AVC/H.264 4:2:0 Long profile</p> <p>Recording Format (Audio)- XAVC QFHD : Linear PCM 2ch, 24bit, 48kHz</p> <p>Recording Frame Rate- XAVC QFHD (3840 x 2160) @29.97p, 25p, 23.98p 100Mbps/60Mbps</p> <p>Recording/Playback Time- XAVC QFHD @LPCM 2ch 100 Mbps</p> <p>Lens-</p> <p>Lens Mount- Fixed</p> <p>Zoom Ratio- 12x (optical), servo</p> <p>Focal Length- f=9.3 - 111.6mm</p> <p>Iris- F2.8 - F4.5 auto/manual selectable</p> <p>Focus- AF/MF selectable- 10 mm to ∞ (Wide) 1000 mm to ∞ (Tele)</p> <p>Image Stabilizer- ON/OFF selectable, shift lens</p> <p>Filter Diameter- M62 mm</p> <p>Streaming- Protocol AVC / RTMP / RTMPS 1,280 x 720 at 3 Mbps 640 x 360 at 1 Mbps</p> <p>Input/Output Audio Input XLR-type 3-pin (female) (x2), line/mic/mic +48 V selectable</p> <p>Video Output Integrated into Multi/Micro USB jack (×1) ,</p>	1

		<p>Composite 1.0Vp-p, 75Ω</p> <p>Audio Output</p> <p>Integrated into Multi/Micro USB jack</p> <p>USB</p> <p>Multi/Micro USB jack (x1)</p> <p>Wi-Fi/NFC</p>	
2	SONY BATTERY FOR CAMCORDER Z90 NP-FV70A battery	<p>Info LITHIUM™ rechargeable battery pack offers extended shooting time compared with camcorder's supplied battery High capacity 6.8 V / 13.0 Wh / 1960 mAh Quick charging with optional ACVQV10 AC Adaptor/Charger, ACTi FORCE battery technology for higher capacity, faster recharging time and more accurate and fast remaining capacity indication</p> <p>Weight: 96 gC</p>	1
3	BATTERY CHARGER FOR CAMCORDER Z90 NP-FV70A BATTERY	<p>Charging Time NP-FH100 (Full Charge / Normal Charge) 190 min. / 130 min. NP-FH70 (Full Charge / Normal Charge) 125 min. / 65 min. NP-FH50 (Full Charge / Normal Charge) 115 min. / 55 min. NP-FP90 (Full Charge / Normal Charge) 175</p>	1
4	SONY FULL ILCE -7 M4 BODY with kit (24-70)	<p>Brand - Sony</p> <p>Model Name- ILCE-7M4 Maximum Webcam Image Resolution 33 MP</p> <p>Photo Sensor Size Full-Frame (35.9 x 23.9 mm) fps</p> <p>Image Stabilisation Optical; Sensor shifts Maximum Shutter Speed ; 2227981 Seconds Minimum Shutter Speed; 44591 Seconds Metering Description Centre Weighted Exposure Control Type; Automatic Form Factor Mirrorless; 33MP Full Frame Exmor R CMOS Sensor; 4K 60p Video Up to 10 fps Shooting</p> <p>ISO 100- 51200 759 AF Points (Wide AF Coverage)</p> <p>10-Bit 4:2:2,</p> <p>S-Cinetone Wireless Communication Technology: Wi-Fi; Compatible Mountings: Sony E</p>	1
5	SONY SEL50F1.8F	<p>Compact, lightweight, easy to carry F1.8 maximum aperture for low-light shots 7-blade circular aperture for beautiful defocus effects 75mm (35 mm equivalent) focal length with APS-C sensor M,</p> <p>MINIMUM FOCUS DISTANCE 0.45 m (1.48 ft)</p> <p>MAXIMUM MAGNIFICATION RATIO (X) 0.14 x</p> <p>FILTER DIAMETER (MM) 49 mm WEIGHT 186 g (6.6 oz)</p>	1
6	SONY SEL35F1.8F	<p>Multi-purpose lens with fast F1.8 aperture</p> <p>MINIMUM FOCUS DISTANCE 0.3 m (0.99 ft)</p> <p>MAXIMUM MAGNIFICATION RATIO (X) 0.15x</p> <p>FILTER DIAMETER (MM) 49 mm WEIGHT 154 g (5.5 oz), Lightweight and compact at around 45 mm long,</p>	1
7	SONY ILCE6700M (18-135)	<p>The α6700 represents a new generation of APS-C camera bodies with a futuristic fusion of AI-based recognition technology, superlative α-series still image quality, plus moviemaking features and performance from Sony's acclaimed Cinema Line.</p>	1

		<p>APS-C format back-illuminated Exmor R CMOS sensor with approximately 26.0 effective megapixels, Advanced BIONZ XR engine boosts overall processing speed by up to 8x3, Innovative AI processing unit for enhanced subject recognition, AF and tracking</p> <p>In-body five-axis image stabilisation with Active Mode for movie shooting.</p> <p>High-level movie performance inherited from the Cinema Line.</p> <p>SENSOR TYPE-APS-C type (23.3 x 15.5 mm), Exmor R CMOS sensor. ISO SENSITIVITY-Still images: ISO 100–32000 (expandable to ISO 50–102400), AUTO (ISO 100–6400, selectable lower limit and upper limit), Movies: ISO 100–32000 equivalent, AUTO (ISO 100–6400, selectable lower limit and upper limit).</p> <p>BATTERY LIFE (STILL IMAGES)- Approx. 550 shots (Viewfinder)/Approx. 570 shots (LCD monitor) (CIPA standard)³⁸,</p> <p>NUMBER OF PIXELS (EFFECTIVE) - Still images: Approx. 26.0 megapixels max.³⁹, Movies: Approx. 19.9 megapixels max.³⁹.</p> <p>MONITOR TYPE-7.5 cm (3.0-type) type TFT</p>	
8	SONY BATTERY FZ100	<p>SPECIFICATIONS</p> <p>Dimensions (W × H × D): Approx. 38.7 x 22.7 x 51.7 mm (1.56 x 0.91 x 2.13), Weight: Approx. 83 g (3.0 oz), Capacity: 7.2 V/16.4 Wh (2,280 mAh)</p>	3
9	DELKIN DEVICES 128GB BLACK UHS-11 SXDC MEMORY CARD	<p>Key Features</p> <p>128GB Storage Capacity UHS-II / V90 / U3 / Class 10 Max Read Speed: 300 MB/s Max Write Speed: 250 MB/s Min Write Speed: 90 MB/s Records 8K, 4K, HDR, and 360° Video Can Withstand 45 Pounds of Impact Water / Dust / Shock / X-Ray Proof Can Withstand Temperature Extremes No Built-In Write-Protect Switch</p>	6
10	MILIBOO 601A TRIPOD	<p>Miliboo MTT601A Ground Level Professional Photography 3 Sections Tripod Stand Aluminum Alloy with 360 Panorama Fluid Hydraulic Bowl Head Max for DSLRTripod Head Type:</p> <p>Fluid Head</p> <p>Included Components: Pack Of 1 Compatible Devices: Camera Special Features 2: Adjustable Special Features 1: Lightweight</p>	3
11	GIMBLE CRANE 4 COMBO	<p>HIGHLIGHTS</p> <p>The CRANE 4 is compact, steady, and capable of carrying large weights. It has a revised wrist rest and handle for better grip, balance indication lights for a quick reminder, and a magnetic wrench and reflector for increased convenience. Its professionalism is seen in its attention to detail.</p> <p>Precise Balance Calibration: New intelligent balance indicator lights Freely Switch: Horizontal and vertical. lock structure</p>	1

		Energy-saving Adjustment: Flexible wrist rest & Extendable sling grip Easier Control: Bluetooth shutter control Intimate Detail Design: Built-in magnetic tightening wrench & protective cover	
12	RODE WIRELESS PRO	The Wireless PRO is the ultimate wireless microphone, packed full of powerful features that offer incredible flexibility for recording pristine audio for your content. Never lose a take with 32-bit float on-board recording, keep all your video and audio flawlessly synchronised with timecode, and capture incredible sounding content effortlessly with intelligent Gain Assist technology. The Wireless PRO delivers everything you could possibly want from a compact wireless microphone system, and much more.	1
13	RODE NTG 5 KIT	Lightweight NTG5 Short Shotgun Mic K-Tek Boom pole with Internal Cable Shock mount and Furry Windshield Phantom Powered Moisture-Resistant for Humid Conditions Compact, Lightweight Housing	1
14	HAWK XLR MALE TO FEMALE CABLE	Model: SXFG-033 XLR Male to XLR Female Cable Microphone Cable Length: 10 Meter / 32.80 Feet Black Color Cable. Professional Microphone Cable XLR Connector with internal strain relief for rugged reliability	1
15	BOOMPOLE PRO FOR GUN MIC	Specifications Mechanical Weight (g) 535 Dimensions (mm) 810 (H) x 40 (W) x 40 (D)	1
16	RODE INTERVIEW GO (REPORTER MIC)	Specifications- Mechanical, Adaptor Dimensions (mm)- Diameter: 23, Width: 42.9, Height: 237, Diameter: 73.3, Width: 73.3, Height: 81.6, Weight (g) - Adaptor- 84 Windshield : 8	1
17	Aperture AL-F7	APUTURE Amaran F7 The Most Versatile On-Camera Lightweight and Compact Extremely Bright LED Light 256 LEDs with 45° Beam Angle 3200 to 9500K Output 1500 Lux Brightness at 3.3' 1 to 100% Dimming Single Colour Temperature/Dimming Knob 15W Maximum Power Draw Accepts L-Series Batteries LCD Info Screen 1/4"-20 Threaded Mounting Hole,	1
18	AMARAN P60X 3LIGHT KIT	CCT- 3200K~6500K, CRI- ≥95, TLCI- ≥97, Beam Angle (Half-Peak Angle), 45°, Max Power Output- ≤60W, Max Power Consumption- ≤78W, Voltage (NP-F Battery)- 6.5V-8.4V DC, Battery Charging (Type), Sony NP-F Style, DC Input, 2-Pin DC Self-locking Waterproof AC Power Cable, Control Methods - On-board, Sidus Link App, Connectivity- Bluetooth 5.0 (Sidus Mesh) ≥80m / 262.5ft, Estimated LED Lifetime (L70) 50,000 Hours	1
19	AMARAN F21C RGBWW MAT LIGHT	CCT 2500K~7500K With its integrated RGBWW chipset, the F21c flexible panel grants you full control over creative lighting decisions, or adding a splash of colour to your scene through its tunable CCT from 2,500K to 7,500K with greenmagenta adjustment, 360° HSI control, 46 colour gel presets, 15 built-in lighting	2

		effects, and 4 user configurable preset buttons. CRI ≥ 95 , Beam Angle- 180° Max Power Output- $\leq 100W$ Max Power Consumption - $\leq 120W$ D-Tap Battery - 12-28.8V DC Battery Compatibility 16.8V, 26V, 28.8V full power output Connectivity -Bluetooth 5.0 (Sidus Mesh) Bluetooth Operating Range- $\geq 80m$ / 262.5ft Firmware Upgradeable - Sidus Link OTA Estimated LED Lifetime (L70) 50,000 Hours 2% over 6,000 Hours	
20	AMARAN COB 60D	CCT 5,600K, Distance 0.5m - No Reflector - Hyper Reflector (Mini) 11,500 lux / 1,068 fc- 134,700 lux / 12,514 fc 1.0m - 2,940 lux / 273 fc,- 37,800 lux / 3,512 fc 3.0m - 344 lux / 32 fc- 4,200 lux / 390 fc	2
21	AMARAN DOME MINI II SOFT BOX SOFTBOX COB 60	Softbox unfolded $\Phi 550 \times 290mm$ (21.6 \times 11.4") Outside diffuser $\Phi 545mm$ (21.5") Inside diffuser $\Phi 175mm$ (9.3") Eggcrate $\Phi 545mm$ (21.5") Gel holder $\Phi 185 \times 65mm$ (7.3 \times 2.6") Net Weight 1.64 kg (3.61 lb) Softbox- Yes	2
22	AMARAN HAND HELD BRACKET FOR COB 60	Battery Handle for amaran COB 60 Series. Compatible with V-Mount Batteries & amaran NP-F Battery Plate. Lightweight Construction (0.3kg / 0.66lbs). Perfect for On-the-Go Lighting	2
23	CAMERA BAG VANGARD ESPIRE 41	Key Features Well-padded all round to keep your kit safe Well organized with multiple pockets for all essentials Secure full zip closure Transforms into an everyday bag by removing the inserts Functionality that doesn't compromise on design	3
24	SIMPEX LIGHT STAND	Simpex Premium Light Stand 8 Ft Universal stand threads are designed to fit most monolights/strobes, continuous lights, and accessories Measuring 3.3 Feet when closed & extends from 4' to 6" For maximum stability, keep tripod leg supports parallel to the ground; supports up to 2.5 Kg,max load. Quickly and easily folds up for efficient storage; requires no effort on assembly	5
25	SIMPEX LIGHT STAND HEAVY 2 PCS KIT WITH BAG KIT LIGHT STAND 008	Simple Storage and Transport. The Stand Collapses Easily and Is Very Lightweight to Carry Folded height: 4 feet ; Maximum height : 13 feet Universal stand threads are designed to fit most moonlights/strobes, continuous lights, and accessories Shock Absorption Springs Mechanism Protects Equipment and Fingers from Damage.	1