

Technical Specifications for Intravital Microscope

| Basic Description | Description |
|---|---|
| Microscope type and Frame | Fixed stage upright microscope Microscope stand with nosepiece focus (stage remaining in a fixed position) |
| N.P. Arm | Nosepiece focusing arm |
| Adaptor | Fixed stage adapter |
| Bulb | Long-life 12V 100W halogen bulb (pre-centred) with an average life of at least 2,000 hrs quantity three |
| Power Supply | External Power supply |
| Hand Switch | Hand switch for light intensity control |
| Cable | Extension cable for halogen lamp housing |
| Cor | Power cord |
| Nosepiece | Swinging motion nosepiece for two objectives without any interference for electrodes or manipulator. Vibration-free counter spring mechanism. Coarse & fine focus knobs per stroke per rotation. Coarse lower limit stopper mechanism & Torque adjustment mechanism |
| TR Head | Trinocular tube with 3-way light path distribution for simultaneous observation & imaging. |
| Stage | A mechanical stage for the microscope |
| Plan SemiApo 4X | U plan semi apochromatic objective 4X/0.13, WD around 17 |
| Plan SemiApo 10X | U Plan Semi Apochromatic objective 10X/0.3, WD around 10 |
| Eyepiece | Wide field eyepiece 10X, focusable |
| Halogen Lamp House | Lamp house for 12V 100W halogen with connecting cable. |
| Condenser | Swing out achromatic condenser NA around 0.9 for 1.25X-100X magnification |
| Fluorescence Turret, minimum 6 position | Universal reflected light illuminator with field stop and aperture stop, including 6-position mirror unit cassette, UV protective shield, shield plate, Allen wrench and indication plate. |
| ND Filter | Neutral density filter 6 |
| ND Filter | Neutral density filter 50 |

| | |
|----------------------|--|
| FL Lamp House | Lamp house for 100W mercury burner with collector lens and connecting cable |
| FL Burner | 100W mercury bulb quantity two |
| FL Power Supply | Power supply unit for Mercury lamp meeting international regulation |
| Cord | Power cord |
| Shutter | Reflected light shutter |
| Green FL Filter | Mirror unit for fluorescence microscopy, wideband interference green excitation, with exciter filter, dichroic beam splitter and barrier filter, including plastic case. |
| Dual Adaptor | Dual lamp house adaptor for mounting two lamp houses simultaneously |
| Beam splitter | 50:50 % beam splitter |
| | Around 0.63X c-mount adaptor |
| Warranty: | The standard warranty for three years. |