Interior Painting, Whitewashing and other Misc. works at Center Laibrary Bu				
S.N/DSR	Particulars	Unit	Qty	Rate
1	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	Sqm	5000.00	
2	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	Sqm	5000.00	
3	Distempering with 1st quality acrylic distemper (ready mixed) having VOC content less than 50 gms/litre, of approved manufacturer, of required shade and colour complete, as per manufacturer's specification.			
3.a	one or more coats	Sqm	5000.00	
3.b	Two or more coats	Sqm	11000.00	
4	Painting with synthetic enamel (spray) paint of approved brand and manufacture of required colour to give an even shade : One or more coats.	Sqm	9700.00	
5	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in- Charge. With cement mortar 1:4 (1 cement : 4 fine sand)	Sqm	30.00	
6	Repairing of old damage Gypsum board false ceiling at different floors including dismantling/removing damaged false ceiling	Sqm	40.00	

Drouiding & fixing LIV stabilized fiberglass rainforced			
dia. G.I plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovigs incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10192 and IS 12866.The sheets shall be opaque or	sqm	15.00	
Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	kg	70.00	
Renewing glass panes, with putty and nails wherever necessary including racking out the old putty: Float glass panes of nominal thickness 4 mm (weight not less than 10kg/sqm)	sqm	40.00	
Renewal of old putty of glass panes (length)	metre	50.00	
Providing & Fxing curtains of required coloure and fabrick of sizeLength X Width - 213.36 cm X 106.68 cm to exixting curtain rods/plmets .	each	60.00	
Providing & Fxing curtains of required coloure and fabrick of size ,Length X Width - 274.32 cm X 106.68 cm to exixting curtain rods/plmets .	each	25.00	
Provoding & Stainless steel SS grade 304, curtain rod 20 mm dia 1.20 mm thick	metre	35.00	
Veritcal Roller Blinds: Providing and Fixing of Roller blinds, made of 100% polyster with acrylic coating and EOS track system and components duly epoxy polyster poweder coated of required designe coloure pattern of of reqired size Make: Vista, Uni,ark, Hunter Douglas.	Sqm	30.00	
<b>PVC Flooring Work :</b> Providing & fixing PVC flooring of 1.5 mm thick approved quality in required shade and coloured (as per	Sam	350.00	
	with polymer coated 'J' or 'L' hooks, bolts & nuts 8mm dia. G.I plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovigs incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10192 and IS 12866.The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified. 2 mm thick flat Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete. Renewing glass panes, with putty and nails wherever necessary including racking out the old putty: Float glass panes of nominal thickness 4 mm (weight not less than 10kg/sqm) Renewal of old putty of glass panes (length) Providing & Fxing curtains of required coloure and fabrick of sizeLength X Width - 213.36 cm X 106.68 cm to exixting curtain rods/plmets . Providing & Fxing curtains of required coloure and fabrick of size, Length X Width - 274.32 cm X 106.68 cm to exixting curtain rods/plmets . Provoding & Stainless steel SS grade 304 , curtain rod 20 mm dia 1.20 mm thick <b>Veritcal Roller Blinds:</b> Providing and Fixing of Roller blinds, made of 100% polyster with acrylic coating and EOS track system and components duly epoxy polyster poweder coated of required designe coloure pattern of of reqired size Make: Vista, Uni,ark, Hunter Douglas. <b>PVC Flooring Work :</b> Providing & fixing PVC flooring of 1.5 mm thick approved quality in required shade and coloured (as per approved sample). The PVC flooring shall be fixed with	with polymer coated 'J' or 'L' hooks, bolts & nuts 8mm dia. G.I plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovigs incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10192 and IS 12866. The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified. 2 mm thick flat Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete. Renewing glass panes, with putty and nails wherever necessary including racking out the old putty: Float glass panes of nominal thickness 4 mm (weight not less than 10kg/sqm) Renewal of old putty of glass panes (length) metre Providing & Fxing curtains of required coloure and fabrick of sizeLength X Width - 213.36 cm X 106.68 cm to exixting curtain rods/plmets. Providing & Fxing curtains of required coloure and fabrick of size ,Length X Width - 274.32 cm X 106.68 cm to exixting curtain rods/plmets. Providing and Fixing of Roller blinds, made of 100% polyster with acrylic coating and EOS track syatem and components duly epoxy polyster poweder coated of required designe coloure pattern of reqired size Make: Vista, Uni,ark, Hunter Douglas. <b>PVC Flooring Work :</b> Providing & fixing PVC flooring of 1.5 mm thick approved quality in required shade and coloured (as per approved sample). The PVC flooring shall be fixed with	with polymer coated T or L' hooks, bolts & nuts 8mm dia. G.I plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovigs incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10192 and IS 12866.The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified. 2 mm thick flat Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete. Renewing glass panes, with putty and nails wherever necessary including racking out the old putty: Float glass panes of nominal thickness 4 mm (weight not less than 10kg/sqm) Renewal of old putty of glass panes (length) Providing & Fxing curtains of required coloure and fabrick of sizeLength X Width - 213.36 cm X 106.68 cm to exixting curtain rods/plmets . Providing & Fxing curtains of required coloure and fabrick of size_Length X Width - 274.32 cm X 106.68 cm to exixting curtain rods/plmets . Providing a Stainless steel SS grade 304 , curtain rod 20 mm dia 1.20 mm thick <b>Vertical Roller Blinds:</b> Providing and Fixing of Roller blinds, made of 100% polyster with acrylic coating and EOS track syatem and components duly epoxy polyster poweder coated of required designe coloure pattern of of reqired size Make: Vista, Uni, ark, Hunter Douglas. <b>PVC Flooring Work :</b> Providing & fixing PVC flooring of 1.5 mm thick approved quality in required shade and coloured (as per approved sample). The PVC flooring shall be fixed with

16	Repairing/replacement of old existing PVC false, including dismentling replacement of damaged false ceiling with New PVC false ceiling all inclussive .	Sqm	5.00	
	Total I/C GST			

## EXURE "X"

	_	
iilding. Amount (Rs.)		
Amount (Rs.)		
	_	
	_	
	-	
	ļ	
	ļ	
	1	



