

SPECIFICATION FOR SERVER

	Intel Xeon E5-2630 v3 2.4GHz, 20M Cache, 8.00 GT/s QPI, Turbo, HT, 8C/16T(85W) Max Mem 1866MHz
1	3.5" Chassis with up to 8 Hard Drives
1	iDRAC Port Card
1	Riser
1	Bezel
1	Performance Optimized
1	2400 MT/s RDIMMs
1	16 GB RDIMM, 2400MT/s, Dual Rank, x4 Data Width
1	Upgrade to Two Intel Xeon E5-2630 v3 2.4GHz, 20M Cache, 8.00 GT/s QPI, Turbo, HT, 8C/16T (85W)
1	iDRAC8 Enterprise, integrated Dell Remote Access Controller, enterprise
1	1.2 TB 10K RPM SAS 12 Gbps 2.5 in Hot-Plug Hard Drive, 3.5 in HYB CARR
1	PERC H 730 Integrated RAID Controller, 1 GB Cache
1	QLogic 2562, Dual Port 8Gb Optical Fibre Channel HBA
2	Up to 135W Heatsink for PowerEdge R530
1	DVD+/-RW, SATA, Internal
1	Dual, Hot-Plug, Redundant Power Supply (1+1), 750W
1	Power Edge Server FIPS TPM 2.0
2	Long Jumper Cord, C13-C14, 4m, 12a (APCC Except ANZ)
11	On -Board LOM 1 GBE (Dual Port for Towers, Quad Port for Racks)
1	winSVR Std. 2012 R2 SNGL OLP NL Academic 2 Processor Operating System
1	Fan for 2 CPUs
1	Ready Rails sliding Rails with Cable Management Arm
1	RAID 5 for H330/H730/H730P (3-8 HDDs or SSDs)