

Name of work: Partition work in Room no. 10 & Room no. 01, Finance Section, Adm

S.No	DESCRIPTION	UNIT	QTY.	RATE
1	Providing and fixing the aluminum partitions with extruded built up standard tubular sections of size 2.5"x1.5" of 16 gauge, fixing with dash fasteners of required dia and size, including necessary filing up the gaps at junctions i.e at top bottom and sides with required EPDM rubber/neoprene gasket etc Aluminium sections shall be smooth ,rust free, straight, mitered and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing /paneling ,c.p brass/stainless steel screws,all complete as per the direction of Engineer in charge. The partition having the 5mm thick glass on top and on botfom 12 mm thick particle board of approved color complete as required/as existing.	Sqft	60.00	
2	Providing and fixing the aluminum Door with extruded built up standard tubular sections of size top, vertical and middle 3.25"×1.75" of 16 gauge, fixing with dash tasteners of required dia and size, including necessary filling up the gaps at junctions i.e at top ,bottom and sides with required EPDM rubber/neoprene gasket etc .Aluminium sections shall be smooth ,rust free, straight, mitered and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing /paneling ,c.p brass/stainless steel screws, all complete as per the direction of Engineer in charge. The door having the 5mm thick glass on top and on bottom 12 mm thick particle board of approved color including p/f the aluminium tower bolt, aldrops,door stopper complete as required/as existing.	Sqft	21.00	
3	Providing and fixing aluminium die cast body tubular type universal hydraulic door closer (having brand logo with ISI, IS : 3564, embossed on the body, door weight upto 35 kg and door width upto 700 mm), with necessary accessories and screws etc. complete.	Each	1.00	

4	Providing and fixing wooden partition 75 mm thick double skin with MS hollow section (18 gauge) framework – 50 mm X 50 mm in max. 600 x600 mm C/C in both direction as required. Partition shall be provided with 12mm thick commercial ply of approved quality duly screened & fixed on both faces on the MS framework. Finished with 1mm thick. Laminate (as approved) on both sides of the partition with necessary horizontal and vertical grooves 6/3 mm (as per approval) finished duly with matching colour matt melamine polish, putty etc. on teak wood /matching wooden batten of 3"x3 " size complete as required including polishing.	Sqm	3.26	
5	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	sqm	50.00	
7	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	sqm	50.00	
8	Wall painting with acrylic emulsion paint, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour (with two or more	Sqm	98.00	
	Total			

Contractor's Sign. with

Annexure 'A'
in. Block

AMOUNT

seal